

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

1 Identification

- · Product Identifier
- · Trade Name: GEN-SIL RTV-45 Aluminum
- · Relevant identified uses of the substance or mixture and uses advised against: Silicone elastomer
- · Product Description: Silicone Sealant
- · Details of the Supplier of the Safety Data Sheet:
- · Manufacturer/Supplier:

Silco Inc.

7635 St. Clair Avenue Mentor, OH 44060 Phone: 440-975-8886 Fax: 440-975-8887

· Emergency telephone number: 440-975-8886

2 Hazard(s) Identification

· Classification of the substance or mixture:



Health hazard

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





· Signal word: Danger

· Hazard-determining components of labeling:

Distillates (petroleum), hydtrotreated middle

Silicon Dioxide

· Hazard statements:

H315+H320 Causes skin and eye irritation.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P331 Do NOT induce vomiting.

If on skin: Wash with plenty of water. P302+P352

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313 Take off contaminated clothing and wash it before reuse. P362+P364 If skin irritation occurs: Get medical advice/attention. P332+P313 If eye irritation persists: Get medical advice/attention. P337+P313

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

30 % of the mixture consists of component(s) of unknown toxicity.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 0Reactivity = 0

HMIS-ratings (scale 0 - 4)



*1 Health = *1 Fire = 0

REACTIVITY Physical Hazard = 0

Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous	· Dangerous Components:		
64742-46-7	Distillates (petroleum), hydtrotreated middle	20-30%	
	♦ Asp. Tox. 1, H304		
	Silicon Dioxide	5-10%	
	♦ Carc. 1B, H350; ♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320		

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

- · Description of first aid measures
- After inhalation:

Supply fresh air; consult doctor in case of complaints.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Wash with soap and water.

If skin irritation occurs, consult a doctor.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. If easy to do so, remove contact lenses if worn.

· After swallowing:

Do not induce vomiting.

Rinse mouth with water.

If vomiting ocurrs, the head should be kept low so that the vomit does not enter the lungs (aspiration). Once the vomiting ceases, place the person in the recovery position with the legs slightly raised.

If symptoms develop and/or persist, seek medical attention.

- Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

Treat symptomatically and supportively.

5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- Special hazards arising from the substance or mixture:

Carbon oxides, Silicon oxides, Formaldehyde

Exposure to combustion products may be a hazard to health.

- · Advice for firefighters
- Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

• Additional information: Cool fire exposed containers with water.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
7631-86-9	Silicon Dioxide	18 mg/m³
64-19-7	Acetic Acid	5 ppm
108-24-7	acetic anhydride	0.5 ppm
70131-67-8	Hydroxy terminated polydimethylsiloxane	190 mg/m³
· PAC-2:		
7631-86-9	Silicon Dioxide	740 mg/m³
		(Contd. on page



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

64-19-7	-7 Acetic Acid 35 ppm		
108-24-7	7 acetic anhydride 15 ppm		
70131-67-8	Hydroxy terminated polydimethylsiloxane	2,100 mg/m³	
· PAC-3:			
7631-86-9	Silicon Dioxide	4,500 mg/m ³	
64-19-7	Acetic Acid	250 ppm	
108-24-7	acetic anhydride	100 ppm	
70131-67-8	Hydroxy terminated polydimethylsiloxane	13,000 mg/m³	

7 Handling and Storage

- · Handling
- · Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles: Keep in properly labelled containers.
- Information about storage in one common storage facility: See Section 10 (Incompatible materials)
- Further information about storage conditions: Keep receptacle tightly sealed.
- · **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.

- · Personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:



Safety glasses with side shields

· Limitation and supervision of exposure into the environment: None

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Paste Color: Silver

Odor: Acetic acid likeOdor threshold: Not determined.pH-value: Not applicable.

Change in condition

Melting point/Melting range: Not determined. Boiling point/Boiling range: Not determined.

· Flash point: None

Flammability (solid, gaseous): Not applicable.
 Ignition temperature: Not applicable
 Decomposition temperature: Not determined.

· **Auto igniting:** Product is not self-igniting.

Danger of explosion:
 Product does not present an explosion hazard.

• Explosion limits:

Lower: Not determined. **Upper:** Not determined.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

· Vapor pressure: Not determined.

Density:

Relative density: 0.96

Vapor density: Not determined. Evaporation rate: Not determined.

· Solubility in / Miscibility with:

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

Organic solvents: 1.8 % VOC content: 1.80 %

· Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided:

Thermal decomposition will result in carbon oxides, silicon oxides and formaldehyde.

· Possibility of hazardous reactions:

Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.

- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: Strong oxidizing agents.
- · Hazardous decomposition products: Formaldehyde

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50	values tha	at are relevant for classification:				
7631-86-9	7631-86-9 Silicon Dioxide					
Oral	LD50	10,000 mg/kg (Rat) (OECD 401)				
Dermal	LD50	5,000 mg/kg (Rabbit) (OECD 402)				
Inhalative	LC50/4 h	>140->2,000 mg/l (Rat) (OCED 403) Maximum attainable concentration, mortality does not appear. 10,000 mg/l (Zebra fish) (OECD 203)				
		10,000 High (Zebra lish) (OLGD 203)				

- · Primary irritant effect:
- On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

İrritant



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

7631-86-9 Silicon Dioxide

3

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

- · Toxicity:
- · Aquatic toxicity:

7631-86-9 Silicon Dioxide

EC50 >1,000 mg/l (Daphnia) (OECD 202)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Additional ecological information:
- General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment:
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport Information

· UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

(Contd. on page 8)

(Contd. on page 9)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

· Transport hazard class(es):

· DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

· Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

Environmental hazards: Not applicable.Special precautions for user: Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· UN "Model Regulation": Non-Regulated Material

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- SARA (Superfund Amendments and Reauthorization):

· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
64742-46-7 Distillates (petroleum), hydtrotreated middle	ACTIVE
7631-86-9 Silicon Dioxide	ACTIVE
64-19-7 Acetic Acid	ACTIVE
108-24-7 acetic anhydride	ACTIVE
70131-67-8 Hydroxy terminated polydimethylsiloxane	ACTIVE
· Hazardous Air Pollutants	
None of the ingredients are listed.	
· California Proposition 65:	
· Chemicals known to cause cancer:	
7631-86-9 Silicon Dioxide	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
New Jersey Right-to-Know List:	
64-19-7 Acetic Acid	
108-24-7 acetic anhydride	
New Jersey Special Hazardous Substance List:	
64-19-7 Acetic Acid	CO, F2
108-24-7 acetic anhydride	CO, F2, R1
Pennsylvania Right-to-Know List:	
7631-86-9 Silicon Dioxide	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

64-19-7	Acetic Acid	
108-24-7	acetic anhydride	
· Pennsylvania Special Hazardous Substance List:		
64-19-7	Acetic Acid	E
108-24-7	acetic anhydride	Е

Carcinogenic categories:

Per Variable Protection Agency): None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





Signal word: Danger

· Hazard-determining components of labeling:

Distillates (petroleum), hydtrotreated middle

Silicon Dioxide

· Hazard statements:

H315+H320 Causes skin and eye irritation.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

National regulations:

None of the ingredients are listed.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/05/2019 Reviewed on 04/05/2019

Trade Name: GEN-SIL RTV-45 Aluminum

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of last revision/ revision number: 04/05/2019 / 6
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

Carc. 1B: Carcinogenicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106