

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

1 Identification

- **Product Identifier**
- **Trade Name: PERI-BOND (PB-3) Almond**
- **Relevant identified uses of the substance or mixture and uses advised against:**
No further relevant information available.
- **Product Description:** Siliconized acrylic caulk
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Silco Inc.
7635 St. Clair Avenue
Mentor, OH 44060
Phone: 440-975-8886
Fax: 440-975-8887
- **Emergency telephone number:** 440-975-8886

2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Carc. 1A H350 May cause cancer.
Repr. 1B H360 May damage fertility or the unborn child.



Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**
BBP
Titanium Dioxide
Quartz (SiO₂)
Chlorothalonil (ISO)
- **Hazard statements:**
H315 Causes skin irritation.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:


This value refers to knowledge of known, established toxicological or ecotoxicological values.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

Chemical characterization: Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous Components:

CAS: 85-68-7	BBP	25-50%
RTECS: TH 9990000	⚠ Repr. 1B, H360; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 1317-65-3	Natural limestone	2-12%

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

CAS: 13463-67-7	Titanium Dioxide ☠ Carc. 2, H351	2-12%
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light ☠ Asp. Tox. 1, H304; ☠ Aquatic Chronic 2, H411; ☠ Skin Irrit. 2, H315; STOT SE 3, H336; Flam. Liq. 4, H227	≤2.5%
CAS: 1336-21-6	Ammonium Hydroxide vPvB ☠ Acute Tox. 3, H331; ☠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400; ☠ Acute Tox. 4, H302	≤2.5%
CAS: 1897-45-6	Chlorothalonil (ISO) ☠ Acute Tox. 2, H330; ☠ Carc. 2, H351; ☠ Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ☠ Skin Sens. 1, H317; STOT SE 3, H335	≤2.5%
CAS: 127087-87-0 RTECS: WZ4750000	Nonylphenol Polyethylene Ethoxylate ☠ Eye Dam. 1, H318; ☠ Aquatic Chronic 2, H411; ☠ Acute Tox. 4, H302; Acute Tox. 4, H332	≤2.5%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO ₂) ☠ Carc. 1A, H350; STOT RE 1, H372; ☠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	≤2.5%

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

Description of first aid measures

General information:

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Remove contaminated clothes and shoes. Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor. Do NOT use solvents or thinners.

After eye contact:

If easy to do so, remove contact lenses if worn. Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do not induce vomiting. If conscious, rinse mouth with water ensuring that the rinse is not swallowed. Seek medical assistance.

Information for doctor

Most important symptoms and effects, both acute and delayed:

Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

May cause an allergic skin reaction.

· **Indication of any immediate medical attention and special treatment needed:**

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 Fire-Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information.

· **Special hazards arising from the substance or mixture:**

Closed containers may explode when exposed to extreme heat.

· **Advice for firefighters**

· **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

· **Additional information:**

Cool fire exposed containers with water.

Do not discharge extinguishing water into the aquatic environment.

6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:**

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Do not touch or walk through spilled material.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· **Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

85-68-7	BBP	15 mg/m ³
13463-67-7	Titanium Dioxide	30 mg/m ³
1336-21-6	Ammonium Hydroxide	61 ppm
107-21-1	Ethylene glycol	30 ppm
9036-19-5	Polyethylene glycol octylphenyl ether	13 mg/m ³
1897-45-6	Chlorothalonil (ISO)	0.13 mg/m ³
127087-87-0	Nonylphenol Polyethylene Ethoxylate	30 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
64742-65-0	Petroleum Base Oil	140 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
111-46-6	Diethylene Glycol	6.9 ppm

(Contd. on page 5)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

84-74-2	Dibutyl phthalate	15 mg/m ³
25322-68-3	Polyethylene Glycol	30 mg/m ³
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	120 mg/m ³
· PAC-2:		
85-68-7	BBP	77 mg/m ³
13463-67-7	Titanium Dioxide	330 mg/m ³
1336-21-6	Ammonium Hydroxide	330 ppm
107-21-1	Ethylene glycol	150 ppm
9036-19-5	Polyethylene glycol octylphenyl ether	140 mg/m ³
1897-45-6	Chlorothalonil (ISO)	1.4 mg/m ³
127087-87-0	Nonylphenol Polyethylene Ethoxylate	330 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
64742-65-0	Petroleum Base Oil	1,500 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
111-46-6	Diethylene Glycol	140 ppm
84-74-2	Dibutyl phthalate	1,600 mg/m ³
25322-68-3	Polyethylene Glycol	1,300 mg/m ³
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	1,300 mg/m ³
· PAC-3:		
85-68-7	BBP	460 mg/m ³
13463-67-7	Titanium Dioxide	2,000 mg/m ³
1336-21-6	Ammonium Hydroxide	2,300 ppm
107-21-1	Ethylene glycol	900 ppm
9036-19-5	Polyethylene glycol octylphenyl ether	830 mg/m ³
1897-45-6	Chlorothalonil (ISO)	8.6 mg/m ³
127087-87-0	Nonylphenol Polyethylene Ethoxylate	2,000 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
64742-65-0	Petroleum Base Oil	8,900 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
111-46-6	Diethylene Glycol	860 ppm
84-74-2	Dibutyl phthalate	9300* mg/m ³
25322-68-3	Polyethylene Glycol	7,700 mg/m ³
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	7,900 mg/m ³

7 Handling and Storage

· Handling

· Precautions for safe handling:

- Ensure good ventilation/exhaustion at the workplace.
- Wear protective equipment.
- Avoid contact with skin, eyes and clothing
- Do not take internally.
- Avoid breathing fume/gas/mist/vapors/spray.
- Keep out of reach of children.
- Open and handle receptacle with care.
- Prevent formation of aerosols.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

- **Information about protection against explosions and fires:** Keep protective respiratory device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

1317-65-3 Natural limestone	
NIOSH	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³
NIOSH TWA	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³ respirable dust
OSHA	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³
OSHA TWA	Short-term value: 5 mg/m ³ Long-term value: 15 mg/m ³ respirable fraction
64742-47-8 Distillates (petroleum), hydrotreated light	
OSHA PEL	Long-term value: 5 mg/m ³
14808-60-7 Quartz (SiO₂)	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.
- **Personal protective equipment**
- **General protective and hygienic measures:**
Do not smoke around this product.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

- Do not eat or drink while handling product.
- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing and wash before reuse.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**



NIOSH/OSHA or EN approved respiratory protection is recommended for use in airborne concentrations exceeding exposure limits.

· **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

· **Limitation and supervision of exposure into the environment:**

- Keep away from drains, surface and ground waters.
- Avoid release into the environment.

* 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Paste

Color:

Almond

· **Odor:**

Acrylic-like

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

- **Odor threshold:** Not determined.
- **pH-value @ 20 °C (68 °F):** 7.5-8.5
- **Change in condition**
 - Melting point/Melting range:** Not determined.
 - Boiling point/Boiling range:** >37.78 °C (>100 °F)
- **Flash point:** >93.89 °C (>201 °F) (Closed Cup)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** ≥435 °C (≥815 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** ≥0.4 Vol %
 - Upper:** ≤3.2 Vol %
- **Vapor pressure @ 20 °C (68 °F):** 2.3 kPa
- **Density @ 20 °C (68 °F):** 1.68 g/cm³ (14.0196 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** Not determined.
- **Evaporation rate:** .33 (butyl acetate = 1)
- **Solubility in / Miscibility with:**
 - Water:** Soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** 15-40 g/s
 - Kinematic:** Not determined.
- **Solvent content:**
 - Solids content:** 82.9 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** Stable under normal conditions.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
When exposed to high temperatures may produce hazardous decomposition products.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** High temperatures and incompatible materials.
- **Incompatible materials:**
Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- **Hazardous decomposition products:**
Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

(Contd. on page 9)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

85-68-7 BBP		
Oral	LD50	2,330 mg/kg (Rat)
1317-65-3 Natural limestone		
Oral	LD50	6,450 mg/kg (Rat)
13463-67-7 Titanium Dioxide		
Oral	LD50	>10,000 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (Rat)
64742-47-8 Distillates (petroleum), hydrotreated light		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
1336-21-6 Ammonium Hydroxide		
Oral	LD50	350 mg/kg (RAT) Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Ureter, Bladder: Other changes.
Inhalative	LC50/96 hours	8.2 mg/l (Pimephales)
127087-87-0 Nonylphenol Polyethylene Ethoxylate		
Oral	LD50	16,000 mg/kg (Rat)
Dermal	LD50	4,490 mg/kg (Rabbit) (24 hr occluded contact)
Inhalative	LC50/96 hours	3.8-6.2 mg/l (Pimephales)
	LC50/48 hrs	9.3-21.4 mg/l (Water flea)
14808-60-7 Quartz (SiO₂)		
Oral	LD50	>22,500 mg/kg (Rat)
Inhalative	LC50/96 hours	1,033 mg/l (Trout)

· **Primary irritant effect:**

· **On the skin:**

Irritant to skin and mucous membranes.
May cause an allergic skin reaction.

· **On the eye:** Irritating effect.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories:**

· **IARC (International Agency for Research on Cancer):**

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

(a) Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials, such as in cosmetics or in paints."

(b) OSHA does not regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 the SDS must convey the fact that Titanium Dioxide is a potential carcinogen to rats.

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

85-68-7	BBP	3
13463-67-7	Titanium Dioxide	2B
1897-45-6	Chlorothalonil (ISO)	2B
14808-60-7	Quartz (SiO ₂)	1
· NTP (National Toxicology Program):		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration):		
None of the ingredients are listed.		

12 Ecological Information

- **Toxicity:**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

13463-67-7 Titanium Dioxide	
EC50	>1,000 mg/l (Water flea)
64742-47-8 Distillates (petroleum), hydrotreated light	
EC50	25 mg/l (Trout) (OECD Test Guideline 203, 96 hour, Static Test)
1336-21-6 Ammonium Hydroxide	
EC50	0.66 mg/l (Daphnia)
	0.66 mg/l (Water flea)
14808-60-7 Quartz (SiO₂)	
EC50	218 mg/l (Green algae)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:**

1336-21-6	Ammonium Hydroxide
-----------	--------------------

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods**

· **Recommendation:**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

· **Uncleaned packaging**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport Information

· **UN-Number:**

· **DOT**

Non-Regulated Material

· **ADR/ADN, IMDG, IATA**

UN3082

· **UN proper shipping name:**

· **DOT**

Non-Regulated Material

· **ADR/ADN**

UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP, Ammonium Hydroxide)

· **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP, Ammonium Hydroxide), MARINE POLLUTANT

· **IATA**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP, Ammonium Hydroxide)

· **Transport hazard class(es):**

· **DOT**

· **Class:**

Non-Regulated Material

· **ADR/ADN**



· **Class:**

9 (M6) Miscellaneous dangerous substances and articles

(Contd. on page 12)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.


Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

· **Label:** 9

· **IMDG, IATA**



· **Class:** 9 Miscellaneous dangerous substances and articles
 · **Label:** 9
 · **Packing group:** Non-Regulated Material
 · **DOT** III
 · **ADR/ADN, IMDG, IATA** Product contains environmentally hazardous substances: BBP
 · **Environmental hazards:** Symbol (fish and tree)
 · **Special marking (ADR/ADN):** Symbol (fish and tree)
 · **Special marking (IATA):** Warning: Miscellaneous dangerous substances and articles
 · **Special precautions for user:** 90
 · **Danger code (Kemler):** F-A,S-F
 · **EMS Number:** Ammonium compounds, alkalis
 · **Segregation groups:** A
 · **Stowage Category**
 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
 · **Transport/Additional information:**

· **ADR/ADN**
 · **Excepted quantities (EQ):** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **IMDG**
 · **Limited quantities (LQ):** 5L
 · **Excepted quantities (EQ):** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 · **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BBP, AMMONIUM HYDROXIDE), 9, III

15 Regulatory Information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
 · **SARA (Superfund Amendments and Reauthorization):**

· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical listings):	
1336-21-6	Ammonium Hydroxide
107-21-1	Ethylene glycol
1897-45-6	Chlorothalonil (ISO)
84-74-2	Dibutyl phthalate
· TSCA (Toxic Substances Control Act):	
85-68-7	BBP
1317-65-3	Natural limestone



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

13463-67-7	Titanium Dioxide
64742-47-8	Distillates (petroleum), hydrotreated light
1336-21-6	Ammonium Hydroxide
107-21-1	Ethylene glycol
9036-19-5	Polyethylene glycol octylphenyl ether
1897-45-6	Chlorothalonil (ISO)
127087-87-0	Nonylphenol Polyethylene Ethoxylate
14808-60-7	Quartz (SiO ₂)
64742-65-0	Petroleum Base Oil
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
111-46-6	Diethylene Glycol
54193-36-1	Poly(methacrylic acid, sodium salt)
84-74-2	Dibutyl phthalate
25322-68-3	Polyethylene Glycol
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica
9014-93-1	Dinonylphenyl polyoxyethylene

· California Proposition 65:

Warning: This product contains a chemical known in the state of California to cause birth defects.

· Chemicals known to cause cancer:

13463-67-7	Titanium Dioxide
1897-45-6	Chlorothalonil (ISO)
14808-60-7	Quartz (SiO ₂)

· Chemicals known to cause reproductive toxicity for females:

84-74-2	Dibutyl phthalate
---------	-------------------

· Chemicals known to cause reproductive toxicity for males:

84-74-2	Dibutyl phthalate
---------	-------------------

· Chemicals known to cause developmental toxicity:

85-68-7	BBP
107-21-1	Ethylene glycol

· New Jersey Right-to-Know List:

85-68-7	BBP
1317-65-3	Natural limestone
13463-67-7	Titanium Dioxide
1336-21-6	Ammonium Hydroxide
107-21-1	Ethylene glycol
1897-45-6	Chlorothalonil (ISO)
14808-60-7	Quartz (SiO ₂)
84-74-2	Dibutyl phthalate
25322-68-3	Polyethylene Glycol

· New Jersey Special Hazardous Substance List:

85-68-7	BBP	CA
1336-21-6	Ammonium Hydroxide	CO
1897-45-6	Chlorothalonil (ISO)	CA

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

14808-60-7	Quartz (SiO ₂)		CA
84-74-2	Dibutyl phthalate		TE

· Pennsylvania Right-to-Know List:

85-68-7	BBP		
1317-65-3	Natural limestone		
13463-67-7	Titanium Dioxide		
1336-21-6	Ammonium Hydroxide		
107-21-1	Ethylene glycol		
1897-45-6	Chlorothalonil (ISO)		
14808-60-7	Quartz (SiO ₂)		
111-46-6	Diethylene Glycol		
84-74-2	Dibutyl phthalate		
25322-68-3	Polyethylene Glycol		

· Pennsylvania Special Hazardous Substance List:

85-68-7	BBP		E
1336-21-6	Ammonium Hydroxide		E
107-21-1	Ethylene glycol		E
1897-45-6	Chlorothalonil (ISO)		E
84-74-2	Dibutyl phthalate		E

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

85-68-7	BBP		C
84-74-2	Dibutyl phthalate		D

· TLV (Threshold Limit Value established by ACGIH):

13463-67-7	Titanium Dioxide		A4
107-21-1	Ethylene glycol		A4
14808-60-7	Quartz (SiO ₂)		A2

· NIOSH-Ca (National Institute for Occupational Safety and Health):

13463-67-7	Titanium Dioxide		
14808-60-7	Quartz (SiO ₂)		

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger

· Hazard-determining components of labeling:

- BBP
- Titanium Dioxide
- Quartz (SiO₂)
- Chlorothalonil (ISO)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: PERI-BOND (PB-3) Almond

Hazard statements:

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

None of the ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of last revision/ revision number: 07/31/2019 / 8

Abbreviations and acronyms:

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 16)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/31/2019

Reviewed on 07/31/2019

Trade Name: **PERI-BOND (PB-3) Almond**

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety and Health
OSHA: Occupational Safety & Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1A: Carcinogenicity – Category 1A
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106