

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

1 Identification

· Product Identifier

· Trade Name: SIL-FLEX 7525 CLEAR

Relevant identified uses of the substance or mixture and uses advised against:

· Product Description: Silicone

· Details of the Supplier of the Safety Data Sheet:

· Manufacturer/Supplier:

Silco Inc.

7635 St. Clair Avenue Mentor, OH 44060 Phone: 440-975-8886 Fax: 440-975-8887

· Emergency telephone number: 440-975-8886

2 Hazard(s) Identification

· Classification of the substance or mixture:



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements:
- Hazard pictograms:



- · Signal word: Warning
- · Hazard-determining components of labeling:

Hydroxy terminated polydimethylsiloxane

· Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

80.1 % of the mixture consists of component(s) of unknown toxicity.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2 Fire = 1

REACTIVITY | O | Physical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · Description: Non-Regulated Material

· Dangerous Components:			
70131-67-8	Hydroxy terminated polydimethylsiloxane	60-90%	
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335		
	3-(trimethoxysilyl)propylamine	2-12%	
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Flam. Liq. 4, H227		

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

First-Aid Measures

- · Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in the side position for transportation.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eve contact:

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

Rinse opened eve for several minutes under running water.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:				
70131-67-8	Hydroxy terminated polydimethylsiloxane 190 r			
13822-56-5	3-(trimethoxysilyl)propylamine 30 mg/r			
67-56-1	1 Methanol 530			
· PAC-2:				
70131-67-8	B Hydroxy terminated polydimethylsiloxane 2,100 m			
13822-56-5	3-(trimethoxysilyl)propylamine 330 mg/r			
67-56-1	1 Methanol 2,100 pp			
PAC-3:				
70131-67-8	B Hydroxy terminated polydimethylsiloxane 13			
13822-56-5	3-(trimethoxysilyl)propylamine 2,000 m			
67-56-1	Methanol 7200* ppm			

7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

- · Control parameters:
- · Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- · Personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

· Limitation and supervision of exposure into the environment: None

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Self leveling Color: Clear Oxime

Odor threshold: Not determined.pH-value: Not available

· Change in condition

Melting point/Melting range: Not available Boiling point/Boiling range: Not available

• *Flash point:* ≥205 °C (≥401 °F)

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

· Ignition temperature: No data available

· Decomposition temperature: Not available

· Auto igniting: Product is not self-igniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: No data available No data available Vapor pressure: Negligible (25°C)

· Density:

 Relative density @ 25 °C (77 °F):
 1.04 g/cm³ (8.6788 lbs/gal)

 Vapor density @ 20 °C (68 °F):
 >1 g/cm³ (>8.345 lbs/gal)

 Evaporation rate:
 <1 (n-Butyl Acetate =1)</td>

· Solubility in / Miscibility with:

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

VOC content: 34 g/l

• Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- Information on toxicological effects:
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:					
13822-56-5 3-(trimethoxysilyl)propylamine					
Oral	LD50 Oral	2,970 ml/kg (Rat)			
Dermal	LD50	11,300 mg/kg (Rat)			

- Primary irritant effect:
- On the skin: Irritant to skin and mucous membranes.
- · On the eve: Irritating effect.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

- · Toxicity:
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.

14 Transport Inform<u>ation</u>

· UN-Number:

· **DOT, ADR/ADN, IMDG, IATA**Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

Transport hazard class(es):

· DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

· Packing group:

· **DOT, ADR/ADN, IMDG, IATA**Non-Regulated Material

Environmental hazards: Not applicable.Special precautions for user: Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

UN "Model Regulation": Non-Regulated Material

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

5 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 Methanol

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

67-56-1 Methanol

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· New Jersey Right-to-Know List:

67-56-1 Methanol

67-56-1 Methanol

· New Jersey Special Hazardous Substance List:

TE, F3

· Pennsylvania Right-to-Know List:

None of the ingredients are listed.

· Pennsylvania Special Hazardous Substance List:

None of the ingredients are listed.

- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

· Signal word: Warning

· Hazard-determining components of labeling:

Hydroxy terminated polydimethylsiloxane

· Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. P337+P313

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of last revision/ revision number: 08/06/2019 / 4

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit





Safety Data Sheet (SDS)
OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/06/2019 Reviewed on 08/06/2019

Trade Name: SIL-FLEX 7525 CLEAR

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106